# New Benner Theatre

### **Technical Specifications and General Information**

Metro Arts @ West Village 97 Boundary St West End Qld 4101

Version 6.1 April 2024



### **Table of Contents**

Table of Contents	2
Disclaimer	3
General Information	4
Stage + Auditorium	5
Seating Bank	5
Stage Dimensions	6
Staging + Rigging	7
Fixed Grid	7
Access Equipment	8
Stage Covers	8
Staging Inventory	8
Stage Masking	10
Elevator / Service Bays / Scenic Dock	10
Other Staging Notes	11
Lighting	12
Control	12
Dimmer / Power Distribution Racks	12
House Lights	12
Stage Luminaires	13
LX Accessories / Hardware	13
Cabling	14
Power	14
Special Effects	14
Other Lighting Notes	15
Sound	16
Control Positions	16
System	16
Speakers	16
Additional Sound Equipment	17
Cabling	18
Sound Notes	18
Vision	19
Projection (Venue Standard)	19
Additional Vision Equipment	19
Communications	20
Talkback System	20
Programme Relay (Video)	20
Programme Relay (Audio)	20
Stage Management	20





Back of House Facilities	21
Dressing Rooms	21
Showers + Bathrooms	21
Laundry + Wardrobe	21
Green Room Facilities	22
Health, Safety + Environment (HSE)	23
Fire Safety	23
Safety	23
Risk Assessment	23
Other	24
Accessibility	24
Storage	24
Rehearsal Rooms / Holding Areas	24
Document History	25

### Disclaimer

The information contained in this document is given in good faith and is believed to be correct. Whilst all reasonable care has been taken in the preparation of this document, the information contained herein is believed, but not guaranteed, to be correct at the time of release. Metro Arts will not be liable for any inaccuracies, omissions, or errors in the content, nor for any loss or damages arising from action taken in reliance on the information.

All measurements are approximate and should be checked on site. Floor areas, dimensions and set-outs are indicative only, are not to scale and are subject to change without notice. Prospective hirers must rely on their own enquiries.



### **General Information**

Address	Metro Arts @ West Village 97 Boundary Street, West End, Qld 4101			
Administration + Box Office	Factory Lane, West Village Email: info@metroarts.com.au Phone: (07) 3002 7100 Postal: 116/45 Mollison St, West End, Qld 4101			
Venue Contacts	Venue + Technical Coor Name: Nathaniel Knig Email: nathaniel@me	ht	Operation Name: Email:	ons Manager Shani Gould shani@metroarts.com.au
Venue Layout	The Ice Cream Factory Upper Factory Lane	Rehearsal Studios		
	Ground	Gallery One Bathroom (incl. acce Window Gallery	ssible bath	room. requires swipe access)
	Community Building Ground	Factory Lane Gallery Two Administration Box Office / Bar		
	Mezzanine	Dressing Rooms Bathroom Shower Laundry Technical Gallery Bio Box		
	Lower Ground	Stage-level Accessible bathroom Green Room/Kitcher Service Bay (via car	nette	

## Stage + Auditorium

### **Seating Bank**

**Retractable Seating System** 



System	Maxwood Technology TX-RPO
Seat Style	Espace 628CC.00 High Back
Number of Rows	7 rows of seating on 6 platforms (when fully extended)
Row Rise	350mm
Row Depth	950mm
Number of Aisles	2 – one at each end
Aisle Width	1015mm
Seat Fabric	Camira Main Line Plus – Prudence IF250
Carpet Fabric	Heckmondwike Supacord Carpet - Purple



#### **Operable Configurations** (Refer to Seating Configurations plans)

Mode	Description	Seating Capacity	Stage Space
1	Fully extended (7 rows)  Rows A to G	<ul> <li>108 general admission seats</li> <li>2 accessible seating areas w/ companion seat</li> <li>2x stage-level</li> </ul>	10600mm (width) x 6000mm (depth)
2	Partially extended (5 rows)  Rows A to E	76 general admission seats 2 accessible seating areas w/ companion seat 2x stage-level	10600mm (width) x 9000mm (depth)
3	Partially extended (3 rows)  Rows A to C	<ul> <li>44 general admission seats</li> <li>2 accessible seating areas w/ companion seat</li> <li>2x stage-level</li> </ul>	10600mm (width) x 11000mm (depth)
4	Fully retracted	Flat floor – no seats	10600mm (width) x 13800mm (depth)

#### **Stage Dimensions**

#### **Stage Description**

Rake	None
Surface	Weathertex sheeting, painted black, over 2x layers of plywood.

#### **Venue Size** (not including under mezzanine balcony – seating bank retracted)

Total Area	147.21m2
Total Width of Venue	10600mm
Total Length of Venue	13800mm

#### Stage Height

2190 110.9111	
Floor to underside of mezzanine balcony (OP)	2300mm
Floor to underside of grid	4360mm
Floor to underside of Rigging Points	4600mm
Total Height of Venue	4760mm

#### **Stage Dimensions** (when seating bank is in Mode 1 – 7 rows)

CL = Centre Line SL = Setting Line, measured 1000mm from the front row of seats (Row A)

CL to PS Wall	5300mm
CL to OP Wall (not including under balcony)	5300mm
CL to OP Wall (including under balcony)	7700mm
SL to US Wall	6000mm




SL to feet of front row of seats (Row A)	1000mm
COVID 19 SL to US Wall	5000mm
COVID 19 SL to front row of seats (Row A)	2000mm

### Staging + Rigging

#### **Fixed Grid**





- Distributed and Point Load must NOT exceed the Working Load Limit
- Total load between mid points of pickups not to exceed 100kg
- Point Load is a single point load. Additional point load must not be loaded within 3m.
- Point Load and Distributed load must not be loaded at the same locations.

Rigging Points	Fifteen (15) 1.5T rigging points, maximum of four (4) to be used at one time. Refer to Rigging Point Plan.



#### **Access Equipment**

Note: access equipment is shared across venues within the precinct and is subject to availability. Clients are encouraged to discuss their access needs with the venue.

Model / Item	Notes		Qnt
Elevated Work Platform			
Genie GS-1330 E-Drive	Self-propelled electric sciss For use in New Benner The Maximum work height (indoors): Max platform height: Lift capacity: Machine Width: Machine Length: Weight:		1
Ladders			
Bailey 1.8m 150kg Fibreglass Platform Ladder (Model: FS13579)	Suited for use in Studio 1 & Standing Platform Area: Weight: Maximum Reach: Load Weight Capacity:	508 x 416mm 17.5kg 3.8m 150kg	1
Gorilla 1.8-3.2m 150kg Fibreglass Dual Purpose Ladder (Model: FDM006-I)	Allocated to Gallery 1 & 2 Weight: Maximum Ladder Length: Minimum Ladder Length: Load Weight Capacity:	12.8kg 3.2m 1.8m 150kg	2
Bailey 2.3 - 4.5m 135kg Aluminium Multi- Purpose Ladder (Model: FS13644)	Allocated to New Benner To Weight: Maximum Ladder Length: Minimum Ladder Length: Load Weight Capacity:	heatre  16.7kg 4.5m 1.2m – 2m (telescopic from floor to top rung) 135kg	1

#### **Stage Covers**

Note: Use of venue's Dance Vinyl requires consideration of its condition as a performance surface. Additionally, use of dance vinyl may incur additional fees for consumable and cleaning. Please contact venue to enquire.

	•
Dance Vinyl	Harlequin Reversible Black/White Dance Vinyl
Daniel Villy	(4) rolls 18m x 2m each

#### **Staging Inventory**

Model / Item	Notes		Qnt
Tables			
Bolero 5ft Diameter Round Centre Folding Table	With black tablecloths to suit	1.5m (5ft)	8
(Model: CC506) product link	Table Top Diameter: Top Colour: Legs Colour:	White Silver	0





	With black or beige table	With black or beige table cloths to suit	
Lifetime 6ft Rectangular Folding Table (Model 2901G) product link	Table Top Dimensions: Top Colour: Legs Colour:	1830mm (L) x 760mm (W) White Silver	5
	With black or beige table	cloths to suit	
Other Trestle Table	Table Top Dimensions Top Colour Legs Colour	1830mm (L) x 760mm (W) White Silver	3
Seating	,		
Bolero Black Steel Bistro Side Chair (Model: GL331) product link	Material: Colour: Dimensions (mm): Weight: Seat Height: Seat Dimensions: Stackable:	Steel Black 855 (H) x 455 (W) x 520 (D) 4.9kg  450mm 360mm (W) x 355mm (D) Yes	48
Marius Black Stool product link	Materials: Colour: Load Capacity: Seat diameter: Width: Seat Height: Stackable:	Plastic with steel legs Black (matte) Yes 100kg 320mm 400mm Yes	10
Black Chairs	Material: Colour: Dimensions (mm): Weight: Seat Height (mm): Seat Dimensions (mm): Stackable:	Plastic Black (matte) 820 (H) x 510 (W) x 480 (D) 5kg 450 420 (W) x 400 (D) Yes	16
Miscellaneous			
Black Lectern	'Art Starts Here' logo mod Metallic gold lettering  Built-in sound integration: Built in light: Lectern Dimensions (mm):	No No 1200 (H) x 600 (W) x 600 (D)	1
	'Art Starts Here' logo mo	unted to front.	

Limited rigging gear, including scaffold couplers, scaffold clamps, round and flat slings, and miscellaneous hardware available at the venue. Please enquire for numbers and specifics prior to using the space.



#### **Stage Masking**

Fabric	Fullness	Location	Size	Qty
Black Wool	50%	Legs	4100mm (H) x 2400mm (W)	8
Black Wool	50%	Upper Mezzanine	2800mm (W) x 2330mm (H)	4
Black Wool	50%	Mezzanine Technical Masking	2240mm (W) x 2050mm (H)	1
Black Wool	50%	Lower Mezzanine	7470mm (W) x 2050mm (H)	2
Black Wool	50%	FOH Entry	2190mm (W) x 2170mm (H)	1
Black Wool Fixed	50%	Tabs / Smother On curtain rail between LX 11 & 12. DS of Cyc	5310mm (W) x 4190mm (H)	2
White Cyc (Filled Cloth) Fixed	Flat	Tabs / Smother On curtain rail between LX 11 & 12.	10600mm (W) x 4190mm (H)	1
Black wool	50%	Seating tabs - covers retracted seating bank	5310mm (W) x 2450 (H)	2

#### **Elevator / Service Bays / Scenic Dock**

The Metro Arts Service Bay is located on Basement Level 2 of the West Village Carpark, **and has a maximum height of 2.3m.** Entry to the carpark is via Mollison Street. The Service Bays back directly onto the Metro Arts dock. Please discuss your access needs with your Event Coordinator prior to your booking period.

Description	Dimensions	
Elevator (from Foyer to NBT)	Door Dimensions (mm) 2000mm (H) x 900mm (W)	Internal Dimensions (mm) 2100 (H) x 1100 (W) x 1380 (D)
Service bay carpark size	2600mm (W) x 5400 (D)	
West Village carpark height clearance	2300mm	
Main FOH Sound Lock Doors	1970mm (H) x 1780mm (W)	
Service bay doors (closest to service bays)	2000mm (H) x 1780mm (W)	
Door from stage to BOH sound lock 2050mm (H) x 1800mm (W)		
Stairs into venue (from service bays)	Four (4) steps to stage level.	2300mm (W)
Ramp (from service bays)  1500mm (W) – closest to service bay 1700mm (W) – door level		vice bay
Narrowest width to access NBT through Loading Dock (Pillar to wall in Loading dock)	ng 1700mm (W)	
Floor to clear speaker 2300mm (H)		





#### **Other Staging Notes**

- + Metro Arts adopts definitions outlined by *Live Performance Australia* when describing rigging work.
- Attaching or suspending items using pre-existing / proprietary systems using a standard method is generally not defined as rigging by WHS regulations. This includes handing technical elements (lighting, sound, vision) from hook clamps, attaching cloths/drapes/banners, attaching scenery with a dedicated attachment point, attaching design elements and/or attaching/running cables.
- + Any rigging work beyond the above scope may require installation and sign-off by a qualified rigger, to be wholly arranged at cost by the client.



## Lighting

#### Control

Lighting Console	ETC Ion Xe with (1) 24" LCD touch screen monitor; and (1) 24" LCD screen monitor
Control Channels	2048 outputs
DMX Splitter	(1) LSC MDRJ 10-way DMX Splitter
Signal Distribution (DMX 512A Field Patching)	512A distributed n Cat6A SFTP terminated as 5 pin XLR
Signal Distribution (DMX 512A Rack Patching)	512A distributed n Cat6A SFTP terminated as RJ 45
Remote	IRFR-BTS ETC iPad control app on iPad wifi 16GB
Control Position	PS of Bio Box Control Desk (standard)

#### **Dimmer / Power Distribution Racks**

Model / Item	Amps	Notes	Qnt
LSC APS (Power Distribution) (Model: CC506)	40A	Location: Technical Gallery, Mezzanine Level (OP)	3
LSC iGen VI (Dimmer) (Model: CC506)	40A	with TruPower Location: Technical Gallery, Mezzanine Level (OP)	3

Patch Rack	LSC Redback Patch (located Technical Gallery, Mezzanine Level (OP)
	(icoatea realimeat caner), mezzaimie zerei (cr.)

#### **House and Auxiliary Lights**

Independent Control	Yes
Control	iPad - Crestron app via wifi (default position bio box) Wall panel - Stage level under Mezzanine (OP) Wall panel - Scenic dock behind stage (PS)
Locations	House Lights - stage, seating bank Auxiliary Lights - upper and lower mezzanine, doors/ entrance and seating bank treads Blues - mezzanine, bio box and back of house
Fade Time	15 sec (Non-adjustable)
DMX Link to console	Yes
Notes	Additional bio box blue lights, and blue-power outlets controlled via Crestron iPad app.  House and auxiliary lights are patched into universe 1.



#### **Stage Luminaires**

Make	Model / Item	Angle	Accessories / Details	Weight	Watts	Qnt.
Profiles						
EK	LED Profile FC Narrow RGBAL (Model: LEDPRO144) manual link	15°-30°	DMX Zoom Lens with shutters	9.7kg	250w	6
EK	LED Profile FC Medium RGBAL (Model: LEDPRO145 manual link	25°-50°	DMX Zoom Lens with shutters	9.7kg	250w	6
Fresnels						
SilverStar	LED Fresnel RGBAL DMX Zoom (Frezno ze-2 RGBAL) (Model: LEDFRE116) manual link	15°-45°	DMX Zoom with barndoors	7.6kg	230w	10
Par Cans						
Showpro	LED LitePAR Pro Quad-12 RGBW (Model: LEDPAR121) manual link	25°	12x 8w RGBW LED with barndoors	3.2kg	180w	18
Сус						
SilverStar	LED CYC2 RGBAL (Model: LEDCYC101) manual link	45 x 60°	Two pixels	10kg	180w	6
Moving Lig	ghts					
SilverStar	Pluto 350 Moving Head Spot (Model: PLUTOO350) manual link	5°-35°	CMY	18.5kg	350w	4
Special Ef	Special Effects / Other					
Martin	Atomic 3000 LED Strobe Model: MARTIN3000) manual link		RBG	7.8kg	740w	1
AVE	UV 18 LED Light Bar Model: AVE LEDBAR-UV19) product link		18 x 4W UV Wash	1.1kg	72w	6

#### LX Accessories / Hardware

Make	Model / Item	Notes	Qnt
Hardware			
Doughty	Boom Arm	300 mm (long), 50 mm OD pipe	18
HME	Boom Base Plates	with casters	6
HME	Metal LX H-Stands	Various sizes	8
Big Show	Shot Bags	10 kg	20

#### **Fixture Accessories**

All lanterns have accessories available. Clients should contact the venue to confirm details and quantities.

- + All fresnels have 4 leaf barn doors
- + All profiles have a range of accessories available including irises and gobo holders.
- + All profiles suit 'B' size gobo apertures only.



### Cabling

240v Extension, 5-pin DMX	The venue has a healthy stock of cabling, including 240v extension leads, and 5-Pin DMX leads venue's standard rig and additional equipment. Please discuss your requirements as additional cabling may be required of events with significant requirements
3-Phase Extensions	None

#### **Power**

3-Phase Outlets	All outlets are 40A 5-pin connections
Stage Level	(1) Tech Panel 001 (DS PS) (1) Tech Panel 002 (US PS) (1) Tech Panel 003 (Scenic Store, behind stage PS) (1) Tech Panel 005 (US OP) (1) Tech Panel 008 (Auditorium PS)
Technical Gallery (Mezzanine OP)	(7) Dimmer Bay – 6 used for dimmer racks
GPOs / Green Power / Blue Power	Located at Technical Panels. Refer to tech plans.

#### **Special Effects**

Make	Model / Item	Details		Watts	Qnt
	2.1 Hazer		Haze machine without compressor		
Unique 2.1 Hazei manual link	DMX: Permitted Fluid(s):	2 Channel (pump vs fan) Unique 2.1 Haze Juice	1500w	1	
	F1600 ProFore	Smoke machine in	flightcase		
Beamz F1600 ProFaze product link	DMX: Permitted Fluid(s):	2 Channel TBC	1600w	1	

Smoke + Haze Approval of Use	Any smoke / haze, dry ice or other that is brought into the venue must be approved prior to use. A safety data sheet will be required for all chemicals. The Venue Manager must be consulted whenever any smoke, fog or haze effects are used. The venue must be informed prior to each use of an effect as to make appropriate arrangements to isolate the fire alarm system appropriately. Metro Arts reserves the right to deny the use of any special effects.
Smoke + Haze Approved Fluids / Fees + Charges	Strictly only approved fluids may be used. Metro Arts can provide approved fluids subject to a consumption fee. Please contact venue to enquire.
Cigarettes / Herbals / Vapourisers	See above. Open flames are prohibited.
Strobe / Lasers	For audience comfort and safety, the use of strobe and/or lasers may require warning notices to be included in event billing and displayed publicly. Metro Arts may require additional documentation prior to approval. Please discuss your event needs with your Event Coordinator.





Pyrotechnics / Flames	Pyrotechnics and naked flames are strictly prohibited in all venues due to installed fire protection systems
Flutter / Confetti	Please discuss your event needs with Metro Arts. Any use of any items that may impose a hazard to the venue air-conditioning system may be refused by Metro Arts. Additional cleaning fees may be charged depending on circumstances.

#### **Other Lighting Notes**

- Limited gel stock provided by the venue. Please contact the venue to arrange a site visit or to enquire stock availability.
- + Battery powered and corded LED work lights are available upon request.
- + Any additional equipment being brought into the venue must be inspected by venue staff prior to installation or use.
- + Additional safety cables/ chains can be found in the tech store. *Enquire numbers before arrival*.
- + All electrical appliances and cables shall be tagged with an appropriate safety tag in accordance with AS 3760:20003.



### Sound

#### **Control Positions**

Standard control position is in the bio box, directly behind the seating bank. The bio box features a three-panel operable glazed all and provides direct access to antennas for wireless microphones

Sound consoles can be placed in other locations by special arrangement in consultation with the venue. Mixing position in the seating bank cannot be achieved. Adequate time must be scheduled to accommodate relocation of the system. Additional cabling required to re-direct signal from wireless microphone antennas.

#### **System**

Primary Mixer	Behringer X32 Digital Mixer		
Secondary Mixer	Allen & Heath Qu-16 Digital Mixer		
Amplifiers	None – self-powered speakers deployed.		
EQ / FX	In-build features of primary mixer.		
Signal Distribution	(2) Behringer SD16 Stage Box (1) Behringer P16-D 8-way Ultranet Distribution		
	27-inch iMac (2019)		
Playback System (Sound + Vision)	System: Mac OS Big Sur 11.2.2 Processor: 3.6GHz 8-core ninth-generation Intel Core i9 processor Turbo Boost up to 5.0GHz. Memory: 64GB of 2666MHz DDR4 memory. Graphics: Radeon Pro Vega 48 with 8GB of HMB2 memory. Storage: 1TB of SSD storage. Display: Retina 5k display.	r with	
The state of the s	16-inch MacBook Pro (2019)		
	System: Mac OS Big Sur 11.7 Processor: 2.6GHz 6-core Intel Core i7 processor with Turbo Boos to 4.5GHz.  Memory: 16GB of 2666MHz DDR4 memory. Graphics: Intel UHD Graphics 630. Storage: 512GB SSD. Display: 3072x1920 at 60.00Hz.	st up	
Playback Software	QLab 4.7 (audio, video, and lighting pro license)		
Fire System PA Ducking System	Yes – required for all events.		

#### **Speakers**

Front of House (Left + Right)	(2) 12" Turbosound NuQ122-AN 2500w (flown)
Centre Fill	(1) 12" Turbosound NuQ122-AN 2500w (flown)
Subwoofers	(2) 15" Turbosound nuQ115B-AN 3000w (floor) positioned under seating bank when in use



#### **Additional Sound Equipment**

Make	Model / Item	Details		Qnt
Additional Sp	peakers			
Turbosound	NuQ122-AN 2-Way 12" Full Range Loudspeaker manual link	Wattage: Type: Nominal Dispersion: Frequency Response: Maximum SPL: Dimensions(mm): Weight	2500w Self-Powered 70° H x 70° V @ -6dB points 55 Hz - 18kHz ± 3dB 50 Hz - 20 kHz -10dB 131dB peak 656 (H) x 374 (W) x 340 (D) 20.2kg	4
Turbosound	TFX122M-AN 12" Stage Monitor manual link	Wattage: Type: Nominal Dispersion: Frequency Response: Maximum SPL: Dimensions(mm): Weight	1100w Self-Powered 60° H x 40° V @ -6dB points 75 Hz – 18kHz ± 3dB 68 Hz – 20 kHz -10dB 125dB peak 302 (H) x 452 (W) x 504 (D) 16.9kg	4
JBL	EON615 15" 2-Way Loudspeaker manual link	Wattage: Type: Nominal Dispersion: Frequency Response: Maximum SPL: Dimensions(mm): Weight	1000w Self-Powered 90° H x 60° V @ -6dB points 39 Hz – 20kHz ± 3dB 50 Hz – 10 kHz -10dB 127dB peak 707 (H) x 439 (W) x 365 (D) 17.69kg	2
Microphone S	Stands			
K&M	259/1 Mic Stand	Extra low level - Blac	k	3
K&M	259 Mic Stand	Low Level – Black		4
K&M	210/2 Boom Mic Stand	Black		8
Rode	DSI Desktop Mic Stand	Black		2
Speaker Stan	ds			
K&M	21435 Speaker Stand	50kg load capacity		2
Music Stand				•
Gravity	Music Stand			2
Stage Boxes				
Behringer	SD16 Digital Stage Box	16 inputs, 8 outputs		2
Microphones	(Wired)	,		
Sennheiser	e865-S	Condenser vocal, su	per-cardioid, switched	2
Sennheiser	e835	Dynamic vocal, cardi	oid	2
Sennheiser	e914	Condenser instrumer	nt, cardioid	3
		1		+





Sennheiser	e902	Dynamic instrument kick drum, cardioid	1
Sennheiser	e906	Dynamic instrument, super-cardioid	3
Behringer	Ultravoice XM8500	Dynamic vocal, cardioid	3
Shure	PG 58	Dynamic vocal, cardioid	2
Shure	SM 58	Dynamic vocal, cardioid	2
Microphones	(Wireless)		
Sennheiser	EQ 145 G3 Kit	Case-mounted	8
Sennheiser	SK 100 G3	Compact bodypack transmitter	8
Sennheiser	HSP 2	Omni-direction condenser headset (beige)	8
Sennheiser	ME 2-II	Omni-directional clip-on lavalier	4
DI Boxes			
Radial	USB Pro	USB to balanced audio direct box	1
Radial	Pro D2	Stereo Passive Direct Box	1
Radial	J48 DI	Active Direct Box	2
Behringer	Ultra-DI Active Inject	Model D1100, 9v battery	3
Alto	Direct Box	DI1, 9v battery	1

#### **Cabling**

240v Extension Leads / XLR	The venue has a healthy stock of cabling, including 240v extension leads and 3-Pin XLR to accommodate the venue's standard rig and additional equipment. Please discuss your requirements as additional cabling may be required of events with significant requirements.
----------------------------	--

#### **Sound Notes**

- + Venue standard speakers must not be adjusted.
- + Users are reminded to continuously monitor noise and exposure levels for personnel and patrons. See core staff or FOH members to access onsite digital sound level meter.



### Vision

#### **Projection (Venue Standard)**

Standard Projector	(1) Epson EB-L615U mounted on Epson ELPMB22 ceiling mount (900mm - 1300mm)
Standard Focus Position	Focused onto upstage scrim. Projector rigged on additional bar DS of LX5.
Standard Focus Image	Approximate image size 5600mm (w) x 3500mm (H) (depending on placement of LX fixtures)
Signal	Data over Ethernet via Epson HDBaseT.
Rigging Positions	Projectors with appropriate rigging equipment can be rigged from any horizontal lighting bar.

#### **Additional Vision Equipment**

No venue standard additional sound equipment.

All stock subject to availability and shared across venue. Please enquire with venue for availabilities.

Make	Model / Item	Details		Qnt
Additional Pro	ojectors			
Epson	EH-TW6700 manual link	Zoom: Throw Ratio: Focus Method: Output:  Resolution: Native Aspect Ratio: Contrast Ratio: Colour Processing: Dimensions(mm): Weight:	1.6x (optical) 1.32 (Zoom: Wide), 2.15 (Zoom: Tele) Manual 3,000 lumens (colour) 3,000 lumens (white) 1080p 16:9 70,000:1 10 bit 310 (D) x 410 (W) x 163 (H) 6.9kg	1
Epson	EB-595Wi(e) (Ultra-Short-Throw) manual link	Zoom: Throw Ratio: Focus Method: Output:  Resolution: Native Aspect Ratio: Contrast Ratio: Colour Processing: Dimensions(mm): Weight:	1.0 – 1.35 (Digital Zoom) 0.27 (Zoom: Wide), 0.37 (Zoom: Tele) Manual 3,300 lumens (colour) 3,300 lumens (white) 1280 x 800 (WXGA) 16:10 10,000:1 10 bit 367 (D) x 375 (W) x 155 (H) 5.5kg	3
Optoma	W460ST (Short-Throw) manual link	Zoom Type: Throw Ratio: Focus Method: Output: Resolution: Native Aspect Ratio: Contrast Ratio: Dimensions(mm): Weight:	Fixed 0.525:1 Manual 4,200 ANSI lumens WXGA 1280 x 800 16:10 20,000:1 245 (D) x 216 (W) x 109 (H) 2.95kg	2
Rigging + Mo	unting Accessories			
Epson	ELPMB22 Ceiling Mount			1
Epson	ELP-FP13 Extension Pole			1



### Communications

#### **Talkback System**

Packs	(6) RTC Universal Beltpack BP-4000 (wired)
Headsets	(6) German MAESTRO GMH D 8.400 D Headset (wired)
Standard Locations	Bio box (talkback can also be wired to any available tech panel)

#### **Programme Relay (Video)**

Camera	Standard low light camera (not IR) – angle from the rear of the auditorium. Closed circuit, full-colour. Fixed.	
Relay Location(s)	Green Room Dressing Rooms	

#### **Programme Relay (Audio)**

Source	Sennheiser MKH416, mounted at rear of auditorium	
Relay Location(s)	Green Room (with local volume control) Dressing rooms (with local volume control) Bio Box (Yamaha MSR100 8", with local volume on unit)	

#### **Stage Management**

Standard stage management position is the Bio Box, located behind the seating bank, featuring 3-panel operable glass window. Alternative positions may be achieved – client to schedule appropriately to relocate position. Systems must be returned to standard at conclusion of event.



### **Back of House Facilities**

#### **Dressing Rooms**

Quantity	Two (2)	
Capacity	Dressing Room 1 – capacity of 5 persons Dressing Room 2 – capacity of 5 persons	
Location	Above green room, accessible via staircase from green room. Additionally accessible from the technical gallery on mezzanine level.	
Facilities	Make-up mirrors with task lighting. Build-in wardrobe and clothes racks. Locally controlled programme relay of stage (vision + audio). Locally controlled air-conditioning. Programmable electronic door security.	

#### **Showers + Bathrooms**

Mezzanine (back of house)	Separate facilities next to dressing rooms, accessed via staircase from green room or technical gallery.  + toilet + hand washing basin + shower	
Ground (back of house)	Accessible bathroom/shower in green room, stage level.  + accessible toilet + hand washing basin, shower, including bench	

#### Laundry + Wardrobe

Washing Machine	(1) Fisher & Paykel Front Loader Washing Machine 8kg (Model: WH8060J3) manual link   guick reference link	
Dryer	(1) Fisher & Paykel Vented Dryer 5kg (Model: DE5060MU2) manual link   quick reference link	
Clothes Racks	Fixed racks located in laundry and dressing rooms.  No mobile racks available.	
Storage	1x lockable cabinet in laundry available, designated for high-risk props. Very limited storage in back of house spaces – please discuss your needs with your Event Coordinator.	
Liquids / Consumables	Metro Arts to provide facilities only. Client responsible for provision of detergent / consumables.	
Notes	Articles must be removed from washer/dryer immediately upon completion of cycle as facilities remain in use by Metro Arts ongoing operations.	





#### **Green Room Facilities**

Location	Stage-level, behind stage (accessed via stage or scenic dock)		
Kitchenette Facilities	Fridge / freezer  Microwave-currently out of service  Zip tap (filtered boiling water)  Small stock of utensils and crockery		
Use	The green room is for the use of the presenter, performers and production personnel only. Family, friends or members of the public must not enter back of house areas without prior approval from Metro Arts. Strictly no consumption of alcohol in back of house areas, including green room and dressing rooms. Strictly no alcohol to be brought onsite.		



### Health, Safety + Environment (HSE)

#### **Fire Safety**

- + All scenery, props, and masking must be suitably flame retarded and be rendered non-flammable to the satisfaction of Metro Arts.
- + No scenery and properties are permitted to block or obstruct designated exits at any time.
- + Flammable liquids, gasses, chemicals, solvents or other dangerous materials are not permitted to be brought on site of the precincts without approval.
- + The use of live flames (including candle) is strictly prohibited across all venues of the precinct. The use of haze or smoke effects is prohibited without prior permission from Metro Arts. Please refer to *Special Effects* under *Lighting*.

#### Safety

- Metro Arts and West Village is strictly a non-smoking precinct. This includes the use of e-cigarettes and vaporizers.
- + Alcohol is <u>not permitted</u> to be consumed before or while on duty. Alcohol is not permitted to be consumed in the back of house areas, including the bio box, green rooms and dressing rooms, unless pre-approved by Metro Arts. Alcohol must not be brought onsite, even if not being consumed in accordance to the venues liquor license. Failure to comply may result in termination of contract.
- + Footwear and clothing must be appropriate to the activity. Enclosed footwear is required at all times during bump-ins/outs. Any barefoot personnel (including performers) must be appropriately risk assessed.
- All electrical appliances and cables shall be tagged with an appropriate safety tag in accordance with AS 3760:20003.
- No single insulated cable is permitted to be connected to any Metro Arts power source. However, set-electrics or other electrical items that work on extra-low voltage are permitted as long as the power supply is tested and tagged and the electrical device has been deemed safe by Metro Art's Technical Coordinator.

#### **Risk Assessment**

A risk assessment must be submitted at least 7 days prior to the first day onsite and must include bump-in / bump-out periods. Entry into the venue may be refused until a risk assessment can be provided.

A comprehensive risk assessment is required during pre-production for all shows and events. The Risk Assessment needs to consider the risks associated with your specific event. It should be submitted to Metro Arts at least seven days prior to the event. Our staff can assist you with this process, including a venue standard sanctioned template.

General considerations include:

- + All equipment brought on site is subject to safety checks by Metro Arts staff prior to installation or use.
- All electrical appliances and cables shall be tagged with an appropriate safety tag in accordance with AS 3760:20003.
- + Overhead equipment (including lighting and scenery) must be rigged by competent persons.
- Rigging of high-risk items and/or equipment must be rigged by a qualified rigger, using appropriately certified equipment.
- + Equipment rigged overhead must be secured with a safety chain or similar redundancy.
- Approved drapes must be of a fire-retardant fabric or treated with an approved fire retardant and with an appropriate label attached to the drape.
- Compressed air may only be used by suitably trained operators.



### Other

#### **Accessibility**

Metro Arts is dedicated to ensuring that our venue is welcoming to all patrons.

Metro Arts is dedicated to ensuring that our vehice is welcoming to an patrons.		
Assistive Listening System	The New Benner Theatre provides a phonic ear radio transmitter system for its patrons. It includes headsets and neck loops to assist with hearing of performances and all seating positions are covered. For more information, contact your Metro Arts Event Coordinator.	
Access	The New Benner Theatre can be accessed by elevator from the Foyer to both the Mezzanine and Stage Level.  For artists, the New Benner Theatre can also be accessed by ramp from the Service Bay. Please contact your Event Coordinator for further details.	
Seating	Accessible seating for patrons is available on both the Mezzanine and Stage Level.	
Auslan Interpreting	Metro Arts can assist with organising an interpreter for your event.  Please contact your Event Coordinator for further details.	
Accessible Bathrooms	There are accessible bathrooms in two locations across Metro Arts  + Green room, stage level (artists only)  + Factory lane (general public)	
Assistance Animals	Assistance animals are welcome in all areas of Metro Arts for both artists and patrons.	
Transport	Public Transport – Metro Arts can be accessed most easily by the 199 and 196 bus routes. Please see <a href="here">here</a> for more public transport options.  Car – West Village's carpark offers 2 hours free parking and both levels are wheelchair accessible and offer easy access to Metro Arts.	
	Arts.	

#### **Storage**

Limited storage space is available back of house. Please discuss your needs with your Metro Arts Event Coordinator.

#### **Rehearsal Rooms / Holding Areas**

Metro Arts has two rehearsal studios located in the historical Peter's ice cream factory. These studios feature full-length mirrors, semi-sprung dance floors and in-built sound systems. Subject to availability, additional fees apply. Please contact your Event Coordinator for more information.



## **Document History**

Revision #	Date	Author	Comments / alterations
6.1	24/06/2024	NK	Minor Updates
6	17/04/2024	NK	Minor Updates
5	11/05/2023	TK	Formatting + general updates.
4	02/07/2022	TK	Formatting + general updates.
3	20/08/2021	TK	Minor updates
2	02/08/2021	TK	Update to include accessibility section
1.1	26/07/2021	TK	Update
1.0	17/12/2020	NS	Release
0.8	28/10/2020	BP	Draft (pre-release)
0.7	11/08/2020	BP	Draft (pre-release)
0.6	06/08/2020	NS	Draft (pre-release)
0.1	08/04/2020	NS	Draft (pre-release)



New Benner Theatre
Technical Specifications

metroarts.com.au

Physical Address Metro Arts @ West Village 111 Boundary St West End Qld 4101 Australia

**Postal Address** Metro Arts 116/45 Mollison St West End, Qld, 4101 Australia

The information contained in this document is given in good faith and is believed to be correct. All measurements are approximate and should be checked on site. To ensure information is up to date, please contact Metro Arts closer to the date of your intended event. © Metro Arts 2020.



